


# FIBERLOCK TECHNOLOGIES

# LAG KOTE® II

## Insulation Repair Products

# ASBESTOS LAGGING ENCAPSULANT


QUALITY



KNOWLEDGE



SCIENCE



FOR PROFESSIONAL USE ONLY  
5 U.S. Gallons(18.925 Liters) Net  
Max Allowable VOC Content\*: 200  
Actual Calculated VOC Content: 189

# 6420

www.fiberlock.com

**CLEANUP:** Tools and drippings should be cleaned with warm soapy water before coating dries. Follow equipment manufacturer's directions to clean spray equipment. Dispose of all waste according to current Local, State and Federal regulations.

**DRYING TIME @ 70°F 50% R.H:** To Touch: 1-2 hour

**COVERAGE:** 125-175 ft<sup>2</sup> per gallon

**PRECAUTIONS:** Close container after each use. Store in a dry place at temperatures between 40°F and 100°F. Approved respirators must be used to prevent inhalation of asbestos fibers that may be present in the air. Protective clothing should be worn. Refer to the Material Safety Data Sheet (MSDS) available from your distributor or at [www.fiberlock.com](http://www.fiberlock.com) for further safety and handling instructions. Careful consideration should be given to all EPA, OSHA, and State regulations in effect at the time of application of Penewet. The EPA, through the Office of Pesticides and Toxic Substances, has issued a report headed "Guidance for Controlling Friable Asbestos Containing Materials in Buildings", EPA 560/5 85-024 June 1985, containing the proper data, cautions and procedures for asbestos control. Copies are available from: TSCA Industry Asst. Office, EPA TS-799, 401 M Street SW, Washington, DC 20460, (202) 554-1404.

CAS NO.	Chemical Ingredients
7732-18-5	Water
13463-67-7	Titanium dioxide
1314-13-2	Zinc oxide
1317-65-3	Calcium carbonate
Not avail.*	Latex resin solids
*Contents partially unknown	

#### CAUTION!

**KEEP OUT OF REACH OF CHILDREN.**

Do not take internally. Close container after each use. Keep from freezing.  
24 hour Emergency "CHEM-TEL" Phone: 1-800-255-3924

**DISCLAIMER:** These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of this product are beyond our control. Neither Fiberlock Technologies, Inc., nor its agents shall be responsible for the use of this product or any procedures or apparatus mentioned. We recommend that the prospective user determine the suitability of **Lag Kote II** for each specific project and for the health and safety of personnel working in the area..

For additional information and/or precautions check Material Safety Data Sheet (MSDS) or Product Data Sheet (PDS) available online at [www.fiberlock.com](http://www.fiberlock.com)

\*Maximum regulatory allowable VOC content for this category of product.

Fiberlock Technologies, Inc.  
Andover, MA 01810  
(800) 342-3755  
[www.fiberlock.com](http://www.fiberlock.com)